



Certified for HP Latex Inks

| | | | |
|-----------------|--|--------------------------------|--|
| Substrate | | DIN 60001 | 100 % cotton |
| Weave | | DIN ISO 9354 | woven fabric |
| Weight approx. | | DIN EN ISO 2286-2 | 400 g/m ² |
| Fire retardancy | | B-s2,d0, NFPA 701, CA 1237, M1 | yes |
| Application | | IN | indoor |
| Width | | DIN EN ISO 2286-1 | max. 220 cm / 87 inch (see overview) |
| Print side | | | outside |
| Roll length | | | 25 ± 0,5 m |
| Type of ink | | | all kinds of solvent inks, UV-curable inks, latex inks |

Advantages

- canvas like fabric
- 100 % cotton
- trimming cold (no fraying)

Applications

- frame tensioning systems
- art reproduction

The material might, depending on humidity and temperature, shrink until 2-3 %. The shrink has to be checked before printing.



All details are nominal values and are subject to change within usual tolerances (± 5 %). The information provided in this document is based on current knowledge and experience. They do not exempt a manufacturer/processor from carrying out their own tests and trials as their in-house handling and manufacturing processes can have a significant range of influences on outcomes. Application, utilisation and processing of products is taking place outside of our control and are therefore the sole responsibility of the manufacturer/processor. date: 04/2024