
















Certified for  
HP Latex Inks

|                  |   |   |   |
|------------------|---|---|---|
| Substrate        |  | DIN 60001   | 100 % polyester   |
| Weave            |  | DIN ISO 9354  | woven fabric  |
| Weight approx.   |  | DIN EN ISO 2286-2   | 255 g/m <sup>2</sup> (without liner)<br>350 g/m <sup>2</sup> (with liner) |
| Fire retardancy  |  |   | no  |
| Application      |  |   | indoor  |
| Width            |  | DIN EN ISO 2286-1   | 100 cm / 39 inch  |
| Print side       |  |   | outside   |
| Roll length      |  |   | 30 ± 0,5 m  |
| Care instruction |  | DIN EN 12956  | scrub resistant (grade 5) according to instruction*                       |
| Type of ink      |  |    | all kinds of solvent inks, UV-curable inks, latex inks                    |

## Advantages

- matt surface
- reverse film easy to remove
- easy to clean
- trimming cold (no fraying)
- easy handling, print & cut
- able to plott

## Applications

- wall covering\*\*

\* please have a look at the cleaning instructions on [www.jm-mediatex.com](http://www.jm-mediatex.com)

\*\* please test in advance; the adhesive behavior depends on the surface applied;  
please have a look at the processing instructions on [www.jm-mediatex.com](http://www.jm-mediatex.com)

